


Abstract

We proposed a new framework named FontCLIPstyler[1] to realize **scene text style transformation**.


Our method could freely change the style of text areas in scene images **using prompts** based on CLIPStyler[2].




Methodology

Previous Work: ClipStyler[2]

- For general image style transfer, and **not applicable to text images**.
- Unable to transform styles to specific areas in the image.**



Proposed Method



1. Network for extracting text masks in images(MaskNet)

- Pre-trained with 2000 images using Unet

2. Transfer semantic style of prompts(StyleNet)

- Optimized with loss function Text-aware Loss

3. Only transform the style of the text area without changing the background(Text-aware Loss)

Text-aware Loss

$$L_{ta} = \lambda_d L_{distance} + \lambda_p L_{patch} + \lambda_r L_{recon}$$

$L_{distance}$ Allows style transformation within a limited region based on distance transformation of the input image.

L_{patch} Transfer semantic style of prompts to text area

L_{recon} Background reconstruction

[1] Honghui Yuan and Keiji Yanai: Font Style Translation in Scene Text Images with CLIPstyler. In: ICPR. 2024

[2] Kwon, G., Ye, J.C.: Clipstyler: Image style transfer with a single text condition. In: CVPR. 2022

[3] Kamra, C.G., Mastan, I.D., Gupta, D.: Sem-cs: Semantic clipstyler for text-based image style transfer. In: ICIP. 2023


Results

1. Generation Results


Input scene images, Input prompts and Generated results



2. Comparison with existing methods



3. Ablation Studies



4. Demo System

Scene Text Style Transfer

Our real-time application allows users to freely select the text in image and using prompt to generate the style scene text.

